



INTERNATIONAL® 9900ix

Product Specifications

Model Configurations	9900ix SFA 6x4	Standard	Maximum
	Front GAW	12,000 lbs	14,000 lbs
	Rear GAW	40,000 lbs	46,000 lbs
	Total GVW	52,000 lbs	60,000 lbs
	Total GCW	90,000 lbs	140,000 lbs

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
185	8111	7325	15436	85	138	53	267.7	27ft. 1in.	28ft. 0in.
222	8177	7387	15564	122	175	53	304.7	31ft. 11in.	32ft. 10in.
234	8195	7404	15599	134	187	53	316.7	33ft. 5in.	34ft. 4in.
246	8213	7421	15634	146	199	53	328.7	35ft. 0in.	35ft. 11in.
258	8232	7437	15669	158	211	53	340.7	36ft. 6in.	37ft. 5in.

Frame Rails	110,000 PSI	10.125"
--------------------	-------------	---------

Frame Reinforcement	80,000; 110,000 PSI Inner "C" Channel	8.625", 9.500"
----------------------------	--	----------------

Front Axle	Meritor	12,000; 13,200; 14,000 lb Capacity
	Dana Spicer	12,000; 14,000 lb Capacity

Front Suspension	Parabolic Taper Leaf w/ Shocks	12,000; 14,000 lb Capacity
-------------------------	-----------------------------------	----------------------------

Brakes	Bendix	Air ABS (4-Channel) Available w/ Traction Control
	Meritor-Wabco	Air ABS (4-Channel) Available w/ Traction Control

Steering	Ross, Sheppard
-----------------	----------------

Exhaust System	Cab or Frame Mounted Vertical or Horizontal Muffler and Tail Pipe, Single Right Side or Dual
-----------------------	---

Electrical System	Leece-Neville	110, 135, 140, 145, 160
--------------------------	---------------	-------------------------



INTERNATIONAL® 9900ix

Product Specifications

		Amp Alternators
	Delco-Remy America Inc.	110, 130, 135 Amp Alternators
	International	1850, 2250, 2600, 2775, 3000 CCA Battery System
	Delphi	2250, 2800, 2850, 3000 CCA Battery System
	Long Life Halogen Headlights	
	Qualcomm	Pre-wire Satellite Communications System
Entertainment System	Panasonic	Premium-Quality Stereo System – w/CD player, weather band, multiple coaxial speakers and Satellite radio from Sirius or XM
		Optional DVD Player
		Optional Monsoon Premium sound system
Fifth Wheel	Fontaine	Air Slide or Stationary
Front End	Tilting Composite Hood	
Paint	Base Coat / Clear Coat	
Clutch	Eaton Fuller, Meritor	
Engine & Equipment	Cummins ISX	453 HP/1450 lb-ft to 600 HP/1850 lb-ft
	Caterpillar C15	435 HP/1550 lb-ft to 525 HP/1850 lb-ft
	Air Cleaner	Dual Element
Transmissions	Eaton Fuller	10, 13, 15, 18 Speed Manual
	Eaton Fuller	10, 13, 18 Speed Automated Manual Ultrashift or Autoshift Series
Rear Axle (Tandem)	Meritor	40,000; 46,000 lb Capacity Available w/ Driver



INTERNATIONAL® 9900ix

Product Specifications

		Controlled Locking Diff
	Dana Spicer	40,000; 46,000 lb Capacity Available w/ Driver Controlled Locking Diff
Rear Suspension (Tandem)	International Air Suspension	40,000 lb Capacity w/ 9.25" Ride Height; 52", 55", 60" Axle Spacing
	Hendrickson Air Suspension	46,000 lb Capacity w/ 9.5" Ride Height; 55", 60" Axle Spacing
	International Multileaf 4-Spring Type	40,000 lb Capacity w/ 52" Axle Spacing
Fuel Tank	100 – 300 U.S. Gallons Total Capacity	Mounted Under Cab, Right and Left, or Right Side
Cab	Conventional Aluminum Cab	119.0" BBC
	Sleeper Cab	Hi-Rise 51", 72" Low-Roof 51" Sky-Rise 72"
	Cabinets	Dresser, Footlocker, Refrigerator, Tower Wardrobe, Utility
Interior Trim	Premium Eagle® American Eagle® Eagle® "Black and Tan" Tuck and Roll	
Mirrors	(02) Rectangular w/ Breakaway Type Brackets	
Driver Seats	A wide variety of seats including:	<ul style="list-style-type: none"> • Air-Suspension • High or Intermediate Back • Swivel • Air Lumbar Support
Passenger Seats	A wide variety of seats including:	<ul style="list-style-type: none"> • Air-Suspension or Non-Suspension • High or Intermediate Back • Swivel



INTERNATIONAL® 9900ix

Product Specifications

		<ul style="list-style-type: none">• Air Lumbar Support
Front Wheels	Painted Steel, Polished Aluminum, Non-Polished Aluminum	22.5", 24.5"; 10 Stud
Rear Wheels	Painted Steel, Polished Aluminum, Non-Polished Aluminum	22.5", 24.5"; 10 Stud
Tires	Michelin, Hankook, Double Coin, Continental	
Optional	<ul style="list-style-type: none">• Factory Installed Auxiliary Power Unit• Factory Installed Silver or Platinum Chrome Accessory Packages• Auxiliary Wiring Packages for Aftermarket Bumper and Air Cleaner Lights• Alcoa Dura Bright Wheels	