

INTERNATIONAL[®] PROSTAR[™]

SPECIFICATIONS

MEASUREMENTS

BBC: 122"
Bumper to Axle: 50"
Wheelbase: 4x2 = 146" - 226"; 6x4 = 160" - 240"

AXLES, FRONT

Meritor Wide-Track 12,000 lb, 13,200 lb,
14,000 lb I-Beam
Meritor Standard Track 13,200 lb and 14,000 lb I-Beam
Dana Spicer Wide-Track 12,000 lb lb I-Beam
Dana Spicer Standard Track 14,000 lb I-Beam
Hendrickson Fabricated Wide Track 12,000 lb.

AXLES, REAR, TANDEM

Meritor Single-Reduction 40,000 lb Capacity
Available with Lube Pump, Aluminum Carriers and DCLD
Meritor Single-Reduction 46,000 lb Capacity
Available with DCLD
Dana Spicer Single-Reduction 40,000 lb Capacity
Available with Lube Pump and DCLD
Dana Spicer Single-Reduction 46,000 lb Capacity
Available with DCLD

SUSPENSION, REAR, AIR TANDEM

IROS 40,000 lb Capacity 52", 55", 60" Axle Spacing
Hendrickson 40,000 or 46,000 lb Capacity, 55" Axle Spacing
Hendrickson 46,000 lb Capacity, 60" Axle Spacing

ENGINES

2007: Cummins ISX: 385 - 525 hp Ratings
2008: Caterpillar C13: 380 - 470 hp Ratings
2008: Caterpillar C15: 435 - 500 hp Ratings
2008: International MaxxForce 300 to over 450 hp Ratings

All Ratings dependant on Engine Manufacturer

Final Ratings

FUEL TANKS

Single 100: 26" Polished and Non Polished Aluminum
Single 125: 26" Polished and Non Polished Aluminum
Dual 100: 26" Polished and Non Polished Aluminum
100 and 125: 26" Polished and Non Polished Aluminum
Dual 125: 26" Polished and Non Polished Aluminum
125 and 150: 26" Polished and Non Polished Aluminum

ABS

Bendix ABS-6; 4-Channel System
Bendix RSP and ESP
Meritor WABCO 4-Channel
Meritor RSC

TRANSMISSIONS

Eaton Fuller 10, 13, 15, 18-Speed Manual
Eaton Fuller AutoShift 10, 18-Speed Manual
Eaton Fuller UltraShift 10-Speed Fully Automated Manual

TIRES

Bridgestone, General, Goodyear, Hankook, Michelin

FIFTH WHEEL

Fontaine Stationary or Air Slide 12", 16", 24" Sliders
(Cast, Stamped, Clean Connect)
Mounting Angles for Stationary and Air Slide

WHEELS - FRONT & REAR

Disc: 22.5", 24.5" Painted Steel, Polished and
Non-Polished Aluminum
Disc: 22.5" Polished Aluminum Styled
Dual Disc: 22.5", 24.5" Painted Steel, Polished
and Non-Polished Aluminum
Dual Disc: 22.5" Polished Aluminum Styled
Single Disc: 22.5" Polished and Non-Polished Aluminum

CABS

Daycab
Hi-Rise Sleeper: 56" Seat to Inside Back of Sleeper
with 37" Wide Bunk
Hi-Rise Sleeper: 73" Seat to Inside Back of Sleeper
with 42" Wide Bunk

MODELS

ProStar
ProStar Premium
ProStar Eagle
ProStar Limited

POPULAR ENHANCEMENT OPTIONS

Aero Package: Chassis Skirts, Roof Air Fairing,
Aero Mirrors, Cab Extenders
Vehicle Information Display
Chassis Mounted Tool Box
Remote Keyless Entry System

**Note: Specifications and descriptions in this literature
are as accurate as known at time of publication, but
are subject to change without notice. 03/2006**



A NAVISTAR COMPANY